

1206 NSK 30x62x16mm yobi 1206 Self aligning ball bearings

Bearing number	1206
Size (mm)	30x62x16
Brand	NSK
Bore diameter (mm)	30
Outer diameter (mm)	62
Width (mm)	16
d	30 mm
D	62 mm
B	16 mm
C	16 mm
r min.	1 mm
da min.	35 mm
Da max.	57 mm
ra max.	1 mm
Weight	0.22 Kg
Basic dynamic load rating (C)	15.8 kN
Basic static load rating (C0)	4.65 kN
(Grease) Lubrication Speed	10 000 r/min
(Oil) Lubrication Speed	12 000 r/min
Calculation factor (A)	0.25
Calculation factor (B)	2.6
Calculation factor (C)	3.9
S1	4.17
Y3	2.5
hidfobi	1206
LangB	1
PCB	45.5
D ₁	62
Y2	3.9
SREX	0
cyl count	14
B	16
CAD	http://service.web2cad.co.jp/pcon/Make-NSK_R8Info=nsk_rb/roller_bearings/self_aligning_bh/cylindrical_bore_asstah.prj?varset=(STAN-), (ORDER=1206), (SD=30), (D=62), (B=16), (R=1.0), (CR1=15800), (CR1=4650), (CR2=1610), (CR2=475), (LG=10000), (LD=12000), (DA1=35.0), (DA2=57.0), (RA=1.0), (E=0.25), (Y2=3.9), (Y3=2.50), (YB=2.60), (MASS=0.220)
hidfTable	eca_NSKAB
Oil rpm	22000
SRE	0
YB	2.6
Mass	0.22
ra	1
GRS rpm	10000
SREX	0.04
groove liner	37.556
D ₂	57
SREN	0
CB	4.65
groove outer	54.868
SREN	0
XB	1
Prod_Type3	SABB_SA_CB
X1	1
da	35
X2	0.65
e	0.25
yobi	1206
r	1
KBRG	1352
CAnG	9.483
cyl dia	7.938
calcort	/bearingguide/html/calculation.jsp