

1213S NTN (Oil) Lubrication Speed 6 000 r/min 65x120x23mm Self aligning ball bearings

| | |
|---------------------------------|-----------|
| rs min | 1.5 mm |
| e | 0.17 |
| Y1 | 3.7 |
| Y2 | 5.7 |
| Y0 | 3.8 |
| Radial clearance class | CN |
| Precision class | P0 |
| Mass | 1.15 kg |
| Dynamic load, C | 31 kN |
| Static load, C0 | 12.5 kN |
| Nlim (oil) | 6.000 rpm |
| Nlim (grease) | 4.800 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| da min | 73 mm |
| Da max | 112 mm |
| ra max | 1.5 mm |
| Bearing number | 1213S |
| Size (mm) | 65x120x23 |
| Brand | NTN |
| Bore Diameter (mm) | 65 |
| Outer Diameter (mm) | 120 |
| Width (mm) | 23 |
| d | 65 mm |

| | |
|-------------------------------|-------------|
| D | 120 mm |
| B | 23 mm |
| C | 23 mm |
| r min. | 1.5 mm |
| da min. | 73 mm |
| Da max. | 112 mm |
| ra max. | 1.5 mm |
| Weight | 1.15 Kg |
| Basic dynamic load rating (C) | 31 kN |
| Basic static load rating (C0) | 12.5 kN |
| (Grease) Lubrication Speed | 4 800 r/min |
| (Oil) Lubrication Speed | 6 000 r/min |
| Calculation factor (e) | 0.17 |
| Calculation factor (Y0) | 3.8 |
| Calculation factor (Y1) | 3.7 |