

# 1314 NSK 70x150x35mm CAng 8.455 Self aligning ball bearings

Bearing number	1314
Size (mm)	70x150x35
Brand	NSK
Bore Diameter (mm)	70
Outer Diameter (mm)	150
Width (mm)	35
d	70 mm
D	150 mm
B	35 mm
C	35 mm
r min.	2.1 mm
da min.	81 mm
Da max.	139 mm
ra max.	2 mm
Weight	3.19 Kg
Basic dynamic load rating (C)	75 kN
Basic static load rating (C0)	27.7 kN
Lubrication Speed (Grease)	4 000 r/min
Lubrication Speed (Oil)	5 000 r/min
Calculation factor (e)	0.22
Calculation factor (YB)	3
Calculation factor (Y2)	4.4
SF1	0.58
Y3	2.8
hi4Y0d1	1314
LangID	1
PCD	121
D	150
Y2	4.4
SREX	0
cyl count	16
R	35
CAD	<a href="http://service.web2cad.co.jp/pcor/Maker-NSK_R8&amp;info=nsk_rb/roller_bearings/self_aligning_bb/cylindrical_bore_asstb-prj&amp;varset={STAN-3, (ORDER=1314), (SD=70), (D=150), (B=35), (R=2.1), (CR1=45000), (COR1=25100), (CR2=7650), (COR2=2830), (LG=4000), (LO=5000), (DA1=81.0), (DA2=139.0), (RA=2.0), (E=0.22), (Y2=4.4), (Y3=2.80), (YB=3.00), (MSS=3.000)}">http://service.web2cad.co.jp/pcor/Maker-NSK_R8&amp;info=nsk_rb/roller_bearings/self_aligning_bb/cylindrical_bore_asstb-prj&amp;varset={STAN-3, (ORDER=1314), (SD=70), (D=150), (B=35), (R=2.1), (CR1=45000), (COR1=25100), (CR2=7650), (COR2=2830), (LG=4000), (LO=5000), (DA1=81.0), (DA2=139.0), (RA=2.0), (E=0.22), (Y2=4.4), (Y3=2.80), (YB=3.00), (MSS=3.000)}</a>
hdTable	ecat_H55AB
d11 rpm	5800
SF1	0
YB	3
masS	3
ra	2
GR1 rpm	4000
SRX	0.88
groove inner	92.733
Q <sub>a</sub>	129
SRIN	0
C8	25.1
groove outer	130.476
SREN	0
X8	1
Prod_Type3	SAB8_SA_CB
X1	1
da	81
X2	0.65
e	0.22
y0d1	1314
r	2.1
KBRG	1352
CAng	8.455
cyl dia	18.256
calcort	/bearingguide/html/calculation.jsp