

16009 NTN fillet radius: 0.6 mm 45x75x10mm Deep groove ball bearings

rs min	0.6 mm
Radial clearance class	CN
Mass	0.17 kg
Dynamic load, C	12.9 kN
Static load, C0	10.5 kN
Fatigue limit load, Cu	0.48 kN
f0	16.2
Nlim (oil)	11.000 rpm
Nlim (grease)	9.200 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.45 Hz
Characteristic rolling element frequency, BSF	9.34 Hz
Characteristic outer ring frequency, BPF0	7.15 Hz
Characteristic inner ring frequency, BRFI	8.85 Hz
da min	49 mm
Da max	71 mm
ra max	0.6 mm
Bearing number	16009

Size (mm)	45x75x10
Brand	NTN
Bore Diameter (mm)	45
Outer Diameter (mm)	75
Width (mm)	10
d	45 mm
D	75 mm
B	10 mm
C	10 mm
r min.	0.6 mm
da min.	49 mm
Da max.	71 mm
ra max.	0.6 mm
Weight	0.171 Kg
Basic dynamic load rating (C)	12.9 kN
Basic static load rating (C0)	10.5 kN
(Grease) Lubrication Speed	9 200 r/min
(Oil) Lubrication Speed	11 000 r/min
Category	Single Row Ball Bearings
BDI Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.17
EAN	4547359010152
Product Group – BDI	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0

Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	45MM Bore; 75MM Outside Diameter; 10MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category – BDI	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	16009
Weight / LBS	0.369
Outer Race Width	0.394 Inch 10 Millimeter
Bore	1.772 Inch 45 Millimeter
Outside Diameter	2.953 Inch 75 Millimeter
bore diameter:	45 mm
finish/coating:	Uncoated
outside diameter:	75 mm
bearing material:	High Carbon Chrome Steel
overall width:	10 mm
cage material:	Steel

bore type:	Round
inner ring width:	10 mm
closure type:	Open
outer ring width:	10 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	9200 rpm
snap ring included:	Without Snap Ring
maximum rpm (oil):	11000 rpm
internal clearance:	CN
fillet radius:	0.6 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	11000 RPM
dynamic load capacity:	12900 N
series:	600
static load capacity:	10500 N
manufacturer product page:	Click here
precision rating:	Class 0