

16026 NSK 130x200x22mm SBRG 0 Deep groove ball bearings

| | |
|---------------------------------|---|
| Bearing number | 16026 |
| Size (mm) | 130x200x22 |
| Brand | NSK |
| Bore Diameter (mm) | 130 |
| Outer Diameter (mm) | 200 |
| Width (mm) | 22 |
| d | 130 mm |
| D | 200 mm |
| B | 22 mm |
| C | 22 mm |
| r min. | 1.1 mm |
| da min. | 136.5 mm |
| Da max. | 193.5 mm |
| fa max. | 1 mm |
| Weight | 2.4 kg |
| Basic dynamic load rating (C) | 75.5 kN |
| Basic static load rating (C0) | 77.5 kN |
| (Grease) Lubrication Speed | 3 000 r/min |
| (Oil) Lubrication Speed | 3 000 r/min |
| Category | Single Row Ball Bearings |
| BDI Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 2.7 |
| SKN | 0029176031304 |
| Product Group - BDI | 809388 |
| Enclosure | Open |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 130MM Bore; 200MM Outside Diameter; 22MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category - BDI | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.59.60 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.nskamericas.com |
| Weight / LBS | 5.952 |
| Bore | 5.118 Inch 130 Millimeter |
| Outside Diameter | 7.874 Inch 200 Millimeter |
| Outer Race Width | 0.866 Inch 22 Millimeter |
| bore diameter: | 130 mm |
| closure type: | Open |
| outside diameter: | 200 mm |
| internal clearance: | Normal Clearance |
| overall width: | 22 mm |
| manufacturer upc number: | 029176031304 |
| bore type: | Round |
| SKN | 8.63 |
| NSK P/N | 16026 |
| length | 1 |
| D | 200 |
| SREX | 0.83 |
| B | 22 |
| CAD | https://service.webcad.co.jp/pcon/maker_login.php?maker=NSK_P&language=j&info=nsk_rb/roller_bearings/deep_groove_bb/single_row_dbbb/open_type_asmtab.prj&varset(STAB=...)_(ORDER=16026)_(SD=130)_(D=200)_(B=22)_(E=1.1)_(CR1=75500)_(COR1=77500)_(FO=16.4)_(LG=3000)_(LD=3600)_(DM1=136.5)_(DA1=0.8)_(DA2=193.5)_(FA=1.0)_(PM55=2.400) |
| da min | 136.5 |
| nsftable | ecat_85000 |
| d11 rpm | 3600 |
| SRE | 0.83 |
| bas5 | 2.4 |
| OSI rpm | 3600 |
| ra | 1 |
| SREX | 0.83 |
| D_a | 193.5 |
| SREN | -0.03 |
| CS | 77.5 |
| fo | 16.4 |
| SREN | -0.03 |
| DE | 181.609 |
| Prod_type3 | 0008_00_07 |
| DA | 16.609 |
| bomp | 0 |
| Z | 17 |
| y001 | 16026 |
| C_code | 75500 |
| ALPHA | 0 |
| SDM | 165 |
| r | 1.1 |
| NSK | 6103 |
| SBRG | 0 |
| D1 | 148.331 |
| calcdirt | /bearingGuide/html/calculation.jsp |