

16028 SKF Precision Class ABEC 1 | ISO P0 210x140x22mm Deep groove ball bearings

Bearing number	16028
Size (mm)	210x140x22
Brand	SKF
Bore Diameter (mm)	210
Outer Diameter (mm)	140
Width (mm)	22
d	140 mm
D	210 mm
B	22 mm
d ₁	163.55 mm
D ₁	185.5 mm
r _{1,2} – min.	1.1 mm
d _a – min.	146 mm
D _a – max.	204 mm
r _a – max.	1 mm
Basic dynamic load rating – C	80.6 kN
Basic static load rating – C ₀	86.5 kN
Fatigue load limit – P _u	2.8 kN
Reference speed	6700 r/min
Limiting speed	4000 r/min
Calculation factor – k _r	0.02
Calculation factor – f ₀	16.5

Category	Single Row Ball Bearings
BDI Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.559
EAN	7316577080455
Product Group – BDI	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	140MM Bore; 210MM Outside Diameter; 22MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category – BDI	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	16028
Weight / LBS	5.637

Outside Diameter	8.268 Inch 210 Millimeter
Outer Race Width	0.866 Inch 22 Millimeter
Bore	5.512 Inch 140 Millimeter
bore diameter:	140 mm
static load capacity:	86.5 kN
outside diameter:	210 mm
precision rating:	Not Rated
overall width:	22 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	22 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1 mm
snap ring included:	Without Snap Ring
maximum rpm:	4000 RPM
internal clearance:	C0
series:	16
dynamic load capacity:	80.6 kN
$d_1 \approx$	163.55 mm
$D_1 \approx$	185.5 mm
$r_{1,2} \text{ min.}$	1.1 mm
$d_a \text{ min.}$	146 mm
$D_a \text{ max.}$	204 mm
$r_a \text{ max.}$	1 mm
Basic dynamic load rating C	80.6 kN
Basic static load rating C_0	86.5 kN

Fatigue load limit P_u	2.8 kN
Calculation factor k_r	0.02
Calculation factor f_θ	16.5
Mass bearing	2.53 kg