

# 16030 SKF 225x150x24mm static load capacity: 98 kN Deep groove ball bearings

Bearing number	16030
Size (mm)	225x150x24
Brand	SKF
Bore Diameter (mm)	225
Outer Diameter (mm)	150
Width (mm)	24
d	150 mm
D	225 mm
B	24 mm
d <sub>1</sub>	174.95 mm
D <sub>1</sub>	199.1 mm
r <sub>1,2</sub> – min.	1.1 mm
d <sub>a</sub> – min.	156 mm
D <sub>a</sub> – max.	219 mm
r <sub>a</sub> – max.	1 mm
Basic dynamic load rating – C	92.3 kN
Basic static load rating – C <sub>0</sub>	98 kN
Fatigue load limit – P <sub>u</sub>	3 kN
Reference speed	6000 r/min
Limiting speed	3800 r/min
Calculation factor – k <sub>r</sub>	0.02
Calculation factor – f <sub>0</sub>	16.5

Category	Single Row Ball Bearings
BDI Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	3.15
EAN	7316577080462
Product Group – BDI	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	150MM Bore; 225MM Outside Diameter; 24MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category – BDI	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	16030
Weight / LBS	6.938

Outside Diameter	8.858 Inch   225 Millimeter
Outer Race Width	0.945 Inch   24 Millimeter
Bore	5.906 Inch   150 Millimeter
bore diameter:	150 mm
static load capacity:	98 kN
outside diameter:	225 mm
precision rating:	Not Rated
overall width:	24 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	24 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	1 mm
snap ring included:	Without Snap Ring
maximum rpm:	3800 RPM
internal clearance:	C0
series:	16
dynamic load capacity:	92.3 kN
$d_1 \approx$	174.95 mm
$D_1 \approx$	199.1 mm
$r_{1,2} \text{ min.}$	1.1 mm
$d_a \text{ min.}$	156 mm
$D_a \text{ max.}$	219 mm
$r_a \text{ max.}$	1 mm
Basic dynamic load rating C	92.2 kN
Basic static load rating $C_0$	98 kN

Fatigue load limit $P_u$	3.05 kN
Calculation factor $k_r$	0.02
Calculation factor $f_\theta$	16.5
Mass bearing	3.14 kg