

208-Z SKF 80x40x18mm EAN 7316576679605 Deep groove ball bearings

Bearing number	208-Z
Size (mm)	80x40x18
Brand	SKF
Bore Diameter (mm)	80
Outer Diameter (mm)	40
Width (mm)	18
d	40 mm
D	80 mm
B	18 mm
d ₁	52.6 mm
D ₂	69.8 mm
r _{1,2} – min.	1.1 mm
d _a – min.	47 mm
d _a – max.	52.5 mm
D _a – max.	73 mm
r _a – max.	1 mm
Basic dynamic load rating – C	33.6 kN
Basic static load rating – C ₀	27 kN
Fatigue load limit – P _u	1.2 kN
Reference speed	15000 r/min
Limiting speed	9500 r/min
Calculation factor – k _r	0.04

Cage Material	Steel
Internal Clearance	C0-Medium
Category	Single Row Ball Bearings
BDI Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.414
EAN	7316576679605
Product Group – BDI	B00308
Enclosure	1 Metal Shield
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	Yes
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Inch – Metric	Metric
Long Description	40MM Bore; 80MM Outside Diameter; 18MM Outer Race Diameter; 1 Metal Shield; Ball Bearing; ABEC 1 ISO P0; Yes Filling Slot; No Snap Ring; No Internal Special Features
Category – BDI	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	208 Z

Weight / LBS	0.9
Outside Diameter	3.15 Inch 80 Millimeter
Outer Race Width	0.709 Inch 18 Millimeter
Bore	1.575 Inch 40 Millimeter
bore diameter:	40 mm
static load capacity:	27 kN
outside diameter:	80 mm
precision rating:	ABEC 3 (ISO Class 6)
overall width:	18 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Single Shield
outer ring width:	18 mm
row type & fill slot:	Single Row Filling Slot
fillet radius:	1 mm
snap ring included:	Without Snap Ring
maximum rpm:	9500 RPM
internal clearance:	C0
series:	20
dynamic load capacity:	33.6 kN
thrust application warning:	This product can not be used in Thrust Applications
$d_1 \approx$	52.6 mm
$D_2 \approx$	69.8 mm
$r_{1,2} \text{ min.}$	1.1 mm
$d_a \text{ min.}$	47 mm
$d_a \text{ max.}$	52.5 mm

D_a max.	73 mm
r_a max.	1 mm
Basic dynamic load rating C	33.6 kN
Basic static load rating C_0	27 kN
Fatigue load limit P_u	1.16 kN
Calculation factor k_r	0.04
Mass bearing	0.39 kg