

2201EEG15 SNR 12x32x14mm Characteristic cage frequency, FTF 0.39 Hz Self aligning ball bearings

| | |
|---|------------|
| d1 | 16.2 mm |
| D1 | 24.8 mm |
| rs min | 0.6 mm |
| e | 0.37 |
| Y1 | 1.69 |
| Y2 | 2.62 |
| Y0 | 1.77 |
| Radial clearance class | CN |
| Precision class | P0 |
| Mass | 0.05 kg |
| Dynamic load, C | 5.6 kN |
| Static load, C0 | 1.27 kN |
| Nlim | 15.000 rpm |
| Min operating temperature, Tmin | -10 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.39 Hz |
| Characteristic rolling element frequency, BSF | 4.26 Hz |
| Characteristic outer ring frequency, BPF0 | 3.92 Hz |
| Characteristic inner ring frequency, BRFI | 6.08 Hz |
| da min | 16 mm |
| Da max | 28 mm |
| ra max | 0.6 mm |

| | |
|---------------------|-----------|
| Bearing number | 2201EEG15 |
| Size (mm) | 12x32x14 |
| Brand | SNR |
| Bore Diameter (mm) | 12.000 |
| Outer Diameter (mm) | 32.000 |
| Width (mm) | 14.000 |
| d | 12.000 mm |
| D | 32.000 mm |
| B | 14.000 mm |
| C | 14.000 mm |