

2213K SNR 65x120x31mm Min operating temperature, Tmin -40 °C Self aligning ball bearings

d1	82.2 mm
D1	102.4 mm
rs min	1.5 mm
Associated sleeve reference	H313
e	0.28
Y1	2.23
Y2	3.45
Y0	2.34
Radial clearance class	CN
Precision class	P0
Mass	1.42 kg
Dynamic load, C	43 kN
Static load, C0	16.4 kN
Fatigue limit load, Cu	3.6 kN
Nref	6.400 rpm
Nlim	7.100 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.67 Hz
Characteristic outer ring frequency, BPF0	7.7 Hz
Characteristic inner ring frequency, BRFI	10.3 Hz

da min	73 mm
da max	79 mm
db min	70 mm
Ce min	8 mm
Da max	112 mm
ra max	1.5 mm
Bearing number	2213K
Size (mm)	65x120x31
Brand	SNR
Bore Diameter (mm)	65.000
Outer Diameter (mm)	120.000
Width (mm)	31.000
d	65.000 mm
D	120.000 mm
B	31.000 mm
C	31.000 mm