

23026EMKW33 SNR Max operating temperature, Tmax 200 °C 130x200x52mm Thrust roller bearings

| | |
|---|-----------|
| B | 52 mm |
| D1 | 182.6 mm |
| rs min | 2 mm |
| Number of lubrication holes | 3 |
| b | 8.9 mm |
| k | 4 mm |
| Associated sleeve reference | H3026 |
| e | 0.22 |
| Y1 | 3.01 |
| Y2 | 4.48 |
| Y0 | 2.94 |
| Radial clearance class | CN |
| Mass | 5.7 kg |
| Dynamic load, C | 565 kN |
| Static load, C0 | 721 kN |
| Fatigue limit load, Cu | 63.4 kN |
| Nref | 3.000 rpm |
| Nlim | 3.600 rpm |
| Min operating temperature, Tmin | -40 °C |
| Max operating temperature, Tmax | 200 °C |
| Characteristic cage frequency, FTF | 0.44 Hz |
| Characteristic rolling element frequency, BSF | 8.47 Hz |

| | |
|---|-------------|
| Characteristic outer ring frequency, BPF0 | 10.62 Hz |
| Characteristic inner ring frequency, BRFI | 13.38 Hz |
| da min | 138.8 mm |
| Da max | 191.2 mm |
| ra max | 2 mm |
| Bearing number | 23026EMKW33 |
| Size (mm) | 130x200x52 |
| Brand | SNR |
| Bore Diameter (mm) | 130.000 |
| Outer Diameter (mm) | 200.000 |
| Width (mm) | 52.000 |
| d | 130.000 mm |
| D | 200.000 mm |
| H | 52.000 mm |