

2308KG15 SNR 40x90x33mm Da max 82 mm Self aligning ball bearings

| | |
|---|------------|
| d1 | 53.7 mm |
| D1 | 76.4 mm |
| rs min | 1.5 mm |
| Associated sleeve reference | H2308 |
| e | 0.43 |
| Y1 | 1.45 |
| Y2 | 2.25 |
| Y0 | 1.52 |
| Radial clearance class | CN |
| Precision class | P0 |
| Mass | 0.9 kg |
| Dynamic load, C | 44.9 kN |
| Static load, C0 | 13.5 kN |
| Nref | 8.500 rpm |
| Nlim | 10.000 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.39 Hz |
| Characteristic rolling element frequency, BSF | 4.27 Hz |
| Characteristic outer ring frequency, BPF0 | 4.71 Hz |
| Characteristic inner ring frequency, BRFI | 7.29 Hz |
| da min | 48 mm |
| da max | 52 mm |
| db min | 45 mm |

| | |
|---------------------|-----------|
| Ce min | 5 mm |
| Da max | 82 mm |
| ra max | 1.5 mm |
| Bearing number | 2308KG15 |
| Size (mm) | 40x90x33 |
| Brand | SNR |
| Bore Diameter (mm) | 40.000 |
| Outer Diameter (mm) | 90.000 |
| Width (mm) | 33.000 |
| d | 40.000 mm |
| D | 90.000 mm |
| B | 33.000 mm |
| C | 33.000 mm |