

29320EX NACHI 100x170x42mm Static Load Rating 1.400.000 N Thrust roller bearings

| | |
|-------------------------------|-----------------|
| Bearing number | 29320EX |
| Size (mm) | 100x170x42 |
| Brand | NACHI |
| Bore Diameter (mm) | 100 |
| Outer Diameter (mm) | 170 |
| Width (mm) | 42 |
| d | 100 mm |
| D | 170 mm |
| T | 42 mm |
| d1 | 146.9 mm |
| r min. | 1.5 mm |
| A | 58 mm |
| B | 27 mm |
| B1 | 38.2 mm |
| C | 20.8 mm |
| D1 | 126 mm |
| Weight | 3.61 Kg |
| Basic dynamic load rating (C) | 435 kN |
| Basic static load rating (C0) | 1400 kN |
| (Grease) Lubrication Speed | 1500 r/min |
| Category | Roller Bearings |
| BDI Inventory | 0.0 |
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |

| | |
|-------------------------|------------------|
| Weight / Kilogram | 3.91 |
| EAN | 4991893556414 |
| Product Group – BDI | B04311 |
| Bore Type | Cylindrical Bore |
| Enclosure | Open |
| Configuration | Single Row |
| Bore Size | 100 mm |
| Outside Diameter | 170 mm |
| Fillet Radius/Chamfer | 1.5 mm |
| Width | 42 mm |
| Dynamic Load Rating | 435.000 N |
| Static Load Rating | 1.400.000 N |
| Limiting Speed – Grease | 1.500 rpm |
| Limiting Speed – Oil | 2.500 rpm |
| da (min) | 130 mm |
| Da (max) | 150 mm |
| ra (max) | 1.5 mm |
| db1 (max) | 105 mm |
| db2 (max) | 107 mm |