

29416E NACHI 80x170x54mm Enclosure Open Thrust roller bearings

| | |
|-------------------------------|-----------|
| Bearing number | 29416E |
| Size (mm) | 80x170x54 |
| Brand | NACHI |
| Bore Diameter (mm) | 80 |
| Outer Diameter (mm) | 170 |
| Width (mm) | 54 |
| d | 80 mm |
| D | 170 mm |
| T | 54 mm |
| d1 | 162 mm |
| r min. | 2.1 mm |
| A | 50 mm |
| B1 | 19 mm |
| B2 | 51 mm |
| C | 26 mm |
| D1 | 117 mm |
| da min. | 120 mm |
| Da max. | 140 mm |
| ra max. | 2 mm |
| Weight | 5.95 Kg |
| Basic dynamic load rating (C) | 480 kN |
| Basic static load rating (C0) | 1490 kN |
| Category | Bearings |
| BDI Inventory | 0.0 |

| | |
|-----------------------|------------------|
| Manufacturer Name | NACHI |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0 |
| Product Group – BDI | B04311 |
| Bore Type | Cylindrical Bore |
| Enclosure | Open |
| Configuration | Single Row |
| Bore Size | 80 mm |
| Outside Diameter | 170 mm |
| Fillet Radius/Chamfer | 2.1 mm |
| Width | 54 mm |
| Dynamic Load Rating | 480.000 N |
| Static Load Rating | 1.490.000 N |
| Limiting Speed – Oil | 2.100 rpm |
| B | 19 mm |
| da (min) | 120 mm |
| Da (max) | 140 mm |
| ra (max) | 2 mm |