

30TAB06-2NK NACHI Bore Size 30 mm 30x62x15mm Thrust ball bearings

| | |
|-------------------------------|------------------|
| Bearing number | 30TAB06-2NK |
| Size (mm) | 30x62x15 |
| Brand | NACHI |
| Bore Diameter (mm) | 30 |
| Outer Diameter (mm) | 62 |
| Width (mm) | 15 |
| d | 30 mm |
| D | 62 mm |
| B | 15 mm |
| C | 15 mm |
| Angle (α) | 60 ° |
| r min. | 1 mm |
| r1 min. | 0.6 mm |
| Weight | 0.21 Kg |
| Basic dynamic load rating (C) | 29.9 kN |
| Basic static load rating (C0) | 46.4 kN |
| Bore Type | Cylindrical Bore |
| Enclosure | Double Seal |
| Configuration | Single Row |
| Bore Size | 30 mm |
| Outside Diameter | 62 mm |
| Width | 15 mm |
| Fillet Radius/Chamfer | 1 mm |
| r1 | 0.6 mm |

| | |
|--------------------------------------|-----------|
| 2B | 30 mm |
| Dynamic Load Rating | 29.900 N |
| Static Load Rating | 46.400 N |
| Limiting Speed – Oil | 3.250 rpm |
| Starting Torque – Grease Lubrication | 20 N·cm |
| Da1 | 47.5 mm |
| Da2 | 54.9 mm |
| da1 | 46.2 mm |
| da2 | 39.7 mm |