

3213A SNR Da max 112 mm 65x120x38.100mm Angular contact ball bearings

| | |
|---|-----------|
| d1 | 84.5 mm |
| D1 | 103.5 mm |
| a | 59.8 mm |
| Contact angle α | 25 ° |
| rs min | 1.5 mm |
| Radial clearance class | CN |
| Precision class | P0 |
| Mass | 1.52 kg |
| Dynamic load, C | 75.1 kN |
| Static load, C0 | 72.7 kN |
| Fatigue limit load, Cu | 4.35 kN |
| f0 | 15.2 |
| Nref | 4.800 rpm |
| Nlim | 5.200 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.42 Hz |
| Characteristic rolling element frequency, BSF | 5.93 Hz |
| Characteristic outer ring frequency, BPF0 | 4.68 Hz |
| Characteristic inner ring frequency, BRFI | 6.32 Hz |
| da min | 73 mm |
| Da max | 112 mm |
| ra max | 1.5 mm |
| Bearing number | 3213A |

| | |
|---------------------|---------------|
| Size (mm) | 65x120x38.100 |
| Brand | SNR |
| Bore Diameter (mm) | 65.000 |
| Outer Diameter (mm) | 120.000 |
| Width (mm) | 38.100 |
| d | 65.000 mm |
| D | 120.000 mm |
| B | 38.100 mm |
| C | 38.100 mm |