

51108 SKF Basic static load rating C0 63 kN 40x60x13mm Thrust ball bearings

Bearing number	51108
Size (mm)	40x60x13
Brand	SKF
Bore Diameter (mm)	40
Outer Diameter (mm)	60
Width (mm)	13
d	40 mm
D	60 mm
H	13 mm
d1	60 mm
r1 min.	0.6 mm
r2 min.	0.6 mm
D1	42 mm
da min.	52 mm
Da max.	48 mm
ra max.	0.6 mm
Weight	0.12 Kg
Basic dynamic load rating (C)	25.5 kN
Basic static load rating (C0)	63 kN
Fatigue load limit (Pu)	2.32
Reference speed	5000 r/min
Limiting speed	7000 r/min
Category	Thrust Ball Bearing
BDI Inventory	0.0

Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.128
EAN	7316577058614
Product Group – BDI	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	ABEC 1 ISO P0
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row
Long Description	40MM Bore 1; 42MM Bore 2; 60MM Outside Diameter; 13MM Height; Ball Bearing; Single Direction; Not Banded; Steel Cage; ABEC 1 ISO P0 Precision
Inch – Metric	Metric
Category – BDI	Thrust Ball Bearings
UNSPSC	31171507
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	51108
Weight / LBS	0.283
Height	0.512 Inch 13 Millimeter
Bore 2	1.654 Inch 42 Millimeter

Overall Height with Aligning Washer	0 Inch 0 Millimeter
Bore 1	1.575 Inch 40 Millimeter
Outside Diameter	2.362 Inch 60 Millimeter
maximum rpm:	7000 RPM
bore diameter:	40 mm
static load capacity:	63 kN
outside diameter:	60 mm
dynamic load capacity:	25.5 kN
overall width:	13 mm
thrust bearing type:	Single-Direction
cage material:	Steel
outside diameter design:	Straight
fillet radius:	0.6 mm
separable or banded:	Separable
series:	511
precision rating:	ABEC 1 (ISO Class Normal)
$d_1 \approx$	60 mm
$D_1 \approx$	42 mm
$r_{1,2} \text{ min.}$	0.6 mm
$d_a \text{ min.}$	52 mm
$D_a \text{ max.}$	48 mm
$r_a \text{ max.}$	0.6 mm
Basic dynamic load rating C	25.5 kN
Basic static load rating C_0	63 kN
Fatigue load limit P_u	2.32 kN
Minimum load factor A	0.02

Mass bearing (including seat washer where applicable)	0.12 kg
---	---------