

51134X NSK 170x215x34mm Basic static load rating (C0) 510 kN Thrust ball bearings

| | |
|-------------------------------|---|
| Bearing number | 51134X |
| Size (mm) | 170x215x34 |
| Brand | NSK |
| Bore Diameter (mm) | 170 |
| Outer Diameter (mm) | 215 |
| Width (mm) | 34 |
| d | 170 mm |
| D | 215 mm |
| T | 34 mm |
| d1 | 213 mm |
| r BSH | 1.1 mm |
| D1 | 172 mm |
| da min. | 197 mm |
| Da max. | 188 mm |
| ra max. | 1 mm |
| Weight | 2.72 Kg |
| Basic dynamic load rating (C) | 135 kN |
| Basic static load rating (C0) | 510 kN |
| Lubrication Speed | 1100 r/min |
| SRI | 8.57 |
| hiyobi | 51134X |
| LangID | 1 |
| D | 215 |
| SREX | 0.005 |
| C | 135 |
| B | 34 |
| CAD | http://service.web2cad.co.jp/pcsw/Make-NSK_NBinfo-nsk_rb/roller_bearings/thrust_bearings/single_direction_tbb/with_flat_seat_asmtab.prj?varset={ORDER=51134X},{SD=170},{D=215},{T=34},{SR=1.1},{CAN=135000},{COM=510000},{CA=13000},{COA=52000},{GR=100},{O1=1700},{S0=213},{O1=172},{S0A=197},{DA=188},{SRA=1.0},{PASS=2.720} |
| hiyobi | 51134X |
| Oil rpm | 1700 |
| SRE | 8.57 |
| hast | 2.72 |
| GRS rpm | 1100 |
| ra | 1 |
| SRI | 0.005 |
| D_3 | 188 |
| SRI | 0 |
| C0 | 510 |
| SREN | 0 |
| D_1 | 172 |
| Prod_Type3 | TB_50_MFS |
| da | 197 |
| Da | 13.875 |
| Z | 33 |
| yobi | 51134X |
| SDM | 192.5 |
| r | 1.1 |
| T | 34 |
| KBRG | 5111 |
| calcUrl | /bearingGuide/html/calculation.jsp |