

# AST 23032CW33 spherical roller bearings

YOU'LL 44,45 Bore Diameter (mm) FIND AN EXTENSIVE 44.45x39x14 Size (mm) SELECTION OF AST 23032CW33 spherical roller bearings FOR SALE.

Size (mm)	44.45x39x14
Bore Diameter (mm)	44,45
Outer Diameter (mm)	39
Width (mm)	14
d	44.45 mm
A	39 mm
A1	14 mm
A3 – H14	3.2 mm
A5	23 mm
B	49.2 mm
Da – H11	119.1 mm
Db1	102 mm
Db2	112 mm
J	105 mm
L	137 mm
H	16 mm
s1	30.2 mm
T	54.2 mm
J6	123 mm
J7	33.5 mm
N4	4 mm
DN	6.5 mm

SWN	7 mm
GN – 1/4-28 SAE-LT	1/428 SAELT
RG – 1/4-28 UNF	1/428 UNF
R1	24.5 mm
Basic dynamic load rating – C	33.2 kN
Basic static load rating – C0	21.6 kN
Fatigue load limit – Pu	0.915 kN
Limiting speed	4300 r/min
Mass bearing unit	1.9 kg
Thread – G2 – 5/16-24 UNF	5/1624 UNF
Hexagonal key size for grub screw – H	3.969 mm
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.13
EAN	7316577755049
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Set Screw
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	9/16 Inch
Relubricatable	Yes
Insert Part Number	YAR 209-112-2F
Seals	M Seal
Housing Configuration	1 Piece Solid

Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	4 Bolt Square Flange Block; 1-3/4" Bore; 5.8" Bolt Circle; 4-1/8" Bolt Spacing; 1 Pie
Other Features	Single Row   Standard Duty   Wide Inner Race   Open End   Has Flinger   Y Bearing
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FY 1.3/4 TF
Weight / LBS	4.7
Bore	1.75 Inch   44.45 Millimeter
Cartridge Pilot Diameter	0 Inch   0 Millimeter
Length Thru Bore	1.938 Inch   49.225 Millimeter
Nominal Bolt Circle Diameter Round	5.8 Inch   148 Millimeter
Bolt Spacing	4.125 Inch   104.78 Millimeter
Cartridge Pilot Depth	0 Inch   0 Millimeter
Housing material	Cast iron
Da	119.1 mm
A3	3.2 mm
N	16 mm
RG	1/4-28 UNF

GN	1/4-28 SAE-LT
Basic dynamic load rating C	33.2 kN
Basic static load rating C0	21.6 kN
Fatigue load limit Pu	0.915 kN
Thread grub screw G2	5/16-24 UNF
Hexagonal key size for grub screw N	3.969 mm
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	14 mm
Recommended diameter for attachment bolts, inch G	0.5625 in
Housing	FY 509 M
Bearing	YAR 209-112-2F
End cover	ECY 209