

AST 5217 angular contact ball bearings

100% Authentic. AST 5217 angular contact ball bearings 41.28 mm B Highest Quality. Certified 71.44 mm d 101.5 mm d1 Supplier.

d	71.44 mm
B	41.28 mm
d1	101.5 mm
e	0.36
Y2	1.67
Y0	0.92
Dynamic load, C	226 kN
Rating life coefficient, A2	1.4
Static load, C0	293 kN
Fatigue limit load, Cu	35.4 kN
Nlim (oil)	3,700 rpm
Nlim (grease)	2,700 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	5.85 Hz
Characteristic outer ring frequency, BPF0	7.12 Hz
Characteristic inner ring frequency, BRFI	9.88 Hz
ra max	3.5 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
UNSPSC	31171527
Weight / Kilogram	1.785
EAN	4547359477658
Product Group	B04334
Precision Class	Standard
Component	Cone
Basic Number	H414249
Number of Tapered Rows	Single Row
Inch – Metric	Inch
Other Features	Heavy Duty
Long Description	Cone; Standard Precision; H414249 Basic Number; 2-13/16" Bore; 1-5/8" Width; Single Row of
Flange Outside Diameter	0 Inch 0 Millimeter
Bore	2.813 Inch 71.45 Millimeter
Outside Diameter	0 Inch 0 Millimeter
Width	1.625 Inch 41.275 Millimeter