

AST AST090 23080 plain bearings

Welcome to 95x170x32 Size (mm) the AST AST090 23080 plain bearings online seller. 95 Bore Diameter (mm) 170 Outer Diameter (mm)

| | |
|-------------------------------|------------------|
| Size (mm) | 95x170x32 |
| Bore Diameter (mm) | 95 |
| Outer Diameter (mm) | 170 |
| Width (mm) | 32 |
| d | 95 mm |
| D | 170 mm |
| B | 32 mm |
| C | 32 mm |
| Angle (α) | 30 ° |
| a | 22.2 mm |
| r min. | 2.1 mm |
| r1 min. | 1.1 mm |
| 2B | 64 mm |
| da min. | 102 mm |
| Da max. | 163 mm |
| ra max. | 1 mm |
| Weight | 2.78 Kg |
| Basic dynamic load rating (C) | 205 kN |
| Basic static load rating (C0) | 225 kN |
| (Grease) Lubrication Speed | 2600 r/min |
| Bore Type | Cylindrical Bore |
| Enclosure | Open |

| | |
|-------------------------|-----------|
| Configuration | Duplex |
| Bore Size | 95 mm |
| Outside Diameter | 170 mm |
| Width | 32 mm |
| Fillet Radius/Chamfer | 2.1 mm |
| r1 | 1.1 mm |
| Dynamic Load Rating | 205,000 N |
| Static Load Rating | 225,000 N |
| Limiting Speed – Grease | 2,600 rpm |
| Limiting Speed – Oil | 3,600 rpm |
| da1 (min) | 107 mm |
| da2 (min) | 102 mm |
| Da1 (max) | 158 mm |
| Da2 (max) | 163 mm |
| ra (max) | 2 mm |
| ra1 (max) | 1 mm |