

# AST AST40 2825 plain bearings

170 Million TIMKEN Manufacturer Name used AST AST40 2825 plain bearings instantly searchable. Shop our large selection of parts based on N/A Minimum Buy Quantity brand, price, 0.0 Inventory description, and location. Order the with stock ...

|                           |                                    |
|---------------------------|------------------------------------|
| Inventory                 | 0.0                                |
| Manufacturer Name         | TIMKEN                             |
| Minimum Buy Quantity      | N/A                                |
| Weight                    | 9.988                              |
| EAN                       | 0883450183789                      |
| Product Group             | M06288                             |
| Number of Mounting Holes  | 4                                  |
| Mounting Method           | V Lock                             |
| Housing Style             | 4 Bolt Pillow Block                |
| Rolling Element           | Spherical Roller Bearing           |
| Housing Material          | Cast Steel                         |
| Expansion / Non-expansion | Expansion                          |
| Mounting Bolts            | 5/8 Inch                           |
| Relubricatable            | Yes                                |
| Insert Part Number        | 22213                              |
| Seals                     | Teflon Labyrinth                   |
| Housing Configuration     | 1 Piece Solid                      |
| Inch – Metric             | Inch                               |
| Other Features            | Double Row   Single Nut   SN Style |

|                               |  |
|-------------------------------|--|
| Long Description              | 4 Bolt Pillow Block; 2-1/4" Bore; 3.15" Base to Center Height; V Lock Mount; Spherical Rol |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Weight / LBS                  | 22   |
| B                             | 3.15 Inch   80 Millimeter  |
| d                             | 2.25 Inch   57.15 Millimeter   |
| Bolt Spacing Minimum          | 7.18 Inch   182.372Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| D                             | 3.36 Inch   85.344 Millimeter  |
| Bolt Spacing Maximum          | 8.56 Inch   217.424Millimeter  |
| Nominal Bolt Center to Center | 7.9 Inch   199.5 Millimeter  |