

# AST AST40 F30260 plain bearings

Can't find what 60 mm d you're looking for AST AST40 F30260 plain bearings ? Our expert Representatives be in contact with you shortly!

d	60 mm
D	110 mm
B	22 mm
rs min	1.5 mm
Radial clearance class	C3
Mass	0.78 kg
Dynamic load, C	52.5 kN
Static load, C0	36 kN
Fatigue limit load, Cu	1.64 kN
f0	14.3
Nlim (oil)	7,000 rpm
Nlim (grease)	6,000 rpm
Min operating temperature, Tmin	-60 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.26 Hz
Characteristic outer ring frequency, BPF0	4.08 Hz
Characteristic inner ring frequency, BRFI	5.92 Hz
da min	68 mm

Da max	102 mm
ra max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.938
Product Group	B04270
Enclosure	Open
Precision Class	ABEC 5   ISO P5
Material – Ball	Steel
Number of Bearings	1 (Single)
Contact Angle	0 Degree
Preload	None
Raceway Style	Not Applicable
Cage Material	Brass
Rolling Element	Ball Bearing
Flush Ground	No
Inch – Metric	Metric
Other Features	Single Row   Deep Groove   C3 Clearance
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Width; Open Enclosure; ABEC 5   ISO P5 Precision; Steel Ball
UNSPSC	31171502
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball Deep Groove
Bore	2.362 Inch   60 Millimeter
Width	0.866 Inch   22 Millimeter

Outside Diameter	4.331 Inch   110 Millimeter
------------------	-----------------------------