

# AST AST40 WC14 plain bearings

AST AST40 WC14 plain bearings Warehouse offers car parts and car accessories. We sell discount online as well as cheap Double Shielded Bearing Style machinery 9 Days or more Days to Ship parts.

Days to Ship	9 Days or more
RoHS	6
Bearing Style	Double Shielded
d	95
D	145
B	24
Basic Dynamic Load Rating Cr(N)	60500
Allowable Rotational Velocity(Grease Lubrication)(rpm)	4500
Basic Static Load Rating Cor(N)	54000
Sealing Structure	Double Shielded
Type	Ball
Bearing Ring Material	Steel
Outer Ring Shape	Flat
Precision	Grade 0
Specifications, Environment	Standard
Load Type	Radial
Number of Raceway Ring Rows	Single Row
Size Standards	Metric System
Transmitter Material	Steel
Retainer Type	Punching
Inner/Outer Ring Material	[Steel] Steel
I.D.(Ø)	95

O.D.(Ø)	145
Width(mm)	24
Basic Dynamic Load Rating(N)	60500
Max. Allowed rpm(rpm)	4500
Rolling Element Material	[Steel] Steel
Basic Load Rating, Static Rating(N)	54000
Clearance sign	CN (standard)
Accuracy(Class)	Class 0
Acoustic Symbol	No
Holder Symbol	No
Symbol of Bearing Ring Shape	No
Seal, Shield Symbols	ZZ
Precision Grade Symbol	No
Special Configurations Code	No
Rubugado Symbol	No
Material Symbol	No
Spacer, Sleeve symbol	No
Types	No
Load Direction	Radial
Outer Ring	With Outer Ring
Combination symbol	No
Low Torque Specification	No
Internal Symbol	No
Torque Symbol	No
Specifications/Environment	Standard