

AST AST50 08FIB06 plain bearings

Online shopping AST AST50 08FIB06 plain bearings from a 120 Outer Diameter (mm) great selection at 65x120x23 Size (mm) Store. ... Accessories. 65 Bore Diameter (mm)

Size (mm)	65x120x23
Bore Diameter (mm)	65
Outer Diameter (mm)	120
Width (mm)	23
d	65 mm
D	120 mm
B	23 mm
C	23 mm
a	4.06 mm
b	3.1 mm
f	2.82 mm
r min.	1.5 mm
r1 min.	0.5 mm
D1	115.21 mm
D2	129.7 mm
Weight	0.990 Kg
Basic dynamic load rating (C)	57 kN
Basic static load rating (C0)	40 kN
(Grease) Lubrication Speed	5300 r/min
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A

UNSPSC	31171504
Weight / Kilogram	0.99
Product Group	B00308
Bore Type	Cylindrical Bore
Configuration	Single Row
Enclosure	Snap Ring Groove with Snap Ring
Bore Size	65 mm
Outside Diameter	120 mm
Width	23 mm
Fillet Radius/Chamfer	1.5 mm
r1	0.5 mm
Snap Ring Width	2.8 mm
Snap Ring Outside Diameter	129.7 mm
D1 (max)	115.2 mm
a (max)	4.1 mm
b (min)	3.1 mm
Dynamic Load Rating	57,000 N
Static Load Rating	40,000 N
Limiting Speed – Grease	5,500 rpm
Limiting Speed – Oil	6,500 rpm
Factor fo	14.4
Radial Clearance	0.008 to 0.028 mm
da (min)	74 mm
Da (max)	111 mm
Dx (min)	131.5 mm
ra (max)	1.5 mm
Cy (max)	6.5 mm