

AST AST650 303812 plain bearings

Advance AST AST650 303812 plain bearings is your source for quality and accessories. shop 399.999 mm Da online for home delivery or 198.438 mm da pick up in one of our 10000 .

da	198.438 mm
Da	399.999 mm
Ca	153.797 mm
A1	222.25 mm
A2	304.8 mm
S	4.763 mm
ba	107.95 mm
H	474.663 mm
H1	241.3 mm
H2	95.25 mm
J min.	628.65 mm
J max.	708.025 mm
J1	133.35 mm
L	831.85 mm
N1	41.275 mm
R1	130.175 mm
R2	46.831 mm
RG	1 NPT
PG	1/4 NPT
h	80.963 mm
Housing	SAW 544
Bearing	23244 CCK/W33

Adapter sleeve assembly	SNW 144×7.13/16
Stabilizing ring	SR-44-38
Labyrinth ring	2 x LOR 165
End plug (suffix Y)	EPR 23
Bearing limiting speed	1500 r/min
P60°	423 kN
P90°	254 kN
P120°	160 kN
P150°	145 kN
P180°	173 kN
Pa	95.2 kN
Mass pillow block	284 kg
Cap bolt	4 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	2749.95 g