

AST AST650 354550 plain bearings

Manufacturers of all are represented 30x17x14 Size (mm) in our partial list of clients. Contact 30 Bore Diameter (mm) Gary for a complete AST AST650 354550 plain bearings list of clients and projects.

Size (mm)	30x17x14
Bore Diameter (mm)	30
Outer Diameter (mm)	17
Width (mm)	14
d	17 mm
D	30 mm
B	14 mm
C	13 mm
F	22 mm
r _{1,2} – min.	0.3 mm
s	0.5 mm
da – min.	19 mm
Da – max.	28 mm
ra – max.	0.3 mm
Basic dynamic load rating – C	9.5 kN
Basic static load rating – C ₀	12.9 kN
Fatigue load limit – Pu	1.5 kN
Limiting speed	9000 r/min
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A

Weight / Kilogram	0.045
EAN	7316577012067
Product Group	B04144
bore diameter:	17 mm
dynamic load capacity:	9.52 kN
outside diameter:	30 mm
static load capacity:	12.9 kN
overall width:	14 mm
maximum rpm:	9000 rpm
needle bearing type:	Machined Bearing with Inner Ring
flanges:	With Flanges
closure type:	Double Sealed
seal material:	Nitrile
number of rows:	One
series:	NA
bearing material:	Steel
lubrication hole type:	Hole on Outer Ring
operating temperature range:	-40 to +210 °F °F
precision rating:	Not Rated
cage material:	Steel
manufacturer upc number:	7316577012067
r _{1,2} min.	0.3 mm
s max.	0.5 mm
d _a min.	19 mm
D _a max.	28 mm
r _a max.	0.3 mm
Basic dynamic load rating C	9.52 kN
Basic static load rating C ₀	12.9 kN

Fatigue load limit Pu	1.53 kN
Mass bearing	0.04 kg