

AST AST650 708535 plain bearings

Offer High 106.362 mm dc Quality Brand AST AST650 708535 plain bearings .Contact Us 110 mm da Online to Get Best Quote.

da	110 mm
db	123.825 mm
dc	106.362 mm
Da	200 mm
Ca	62.89 mm
A1	120.65 mm
A2	165.1 mm
S	4.763 mm
ba	50.006 mm
H	244.475 mm
H1	125.425 mm
H2	52.388 mm
J min.	320.675 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	67.866 mm
R2	31.75 mm
RG	3/8 NPT
PG	1/4 NPT
h	45.244 mm
Housing	SAFS 222

Bearing	22222 E
Lock nut	AN 22
Lock washer	W 22
Stabilizing ring	SR-22-19
Labyrinth ring (db shaft position)	LOR 121
PosiTrac Plus contact element (db shaft position)	B10724-122
Labyrinth ring (dc shaft position)	LOR 113
PosiTrac Plus contact element (dc shaft position)	B10724-113
End plug (suffix Y)	EPR 14
Max. speed for PosiTrac Plus seal	1150 r/min
P60°	178 kN
P90°	107 kN
P120°	66.7 kN
P150°	59.6 kN
P180°	72.5 kN
Pa	46.7 kN
Mass pillow block	50.3 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	0.75 in
Initial grease fill	481.95 g