

AST NJ2208 ETN cylindrical roller bearings

Enjoy High 32.6 mm s1 Margins on Competitive 50 mm d Pricing.Great Wholesale Products at 50 Bore Diameter (mm) Low Costs.

Bore Diameter (mm)	50
d	50 mm
s1	32.6 mm
A	58 mm
A1	38 mm
B	51,6 mm
G	16 mm
H	114,5 mm
H1	57.2 mm
H2	22 mm
J	157,5 mm
L	206 mm
N	26,5 mm
N1	20 mm
Weight	2,95 Kg
Basic dynamic load rating (C)	35,1 kN
Basic static load rating (C0)	23,2 kN
Fatigue load limit (Pu)	0,98
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	2.95

EAN	7316570925890
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	16 Millimeter
Relubricatable	Yes
Insert Part Number	YAR 210-2F
Seals	M Seal
Housing Configuration	1 Piece Solid
Inch – Metric	Metric
Other Features	Single Row Y Bearing With Grub Screw
Long Description	2 Bolt Pillow Block; 50MM Bore; 57.2MM Base to Center Height; Set Screw Mount; Ball Bearing; Relubri
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer Item Number	SYJ 50 TF
Weight / LBS	6.5
Base to Center Height	2.252 Inch 57.2 Millimeter
Length Thru Bore	2.031 Inch 51.59 Millimeter

Bolt Spacing Minimum	0 Inch 0Millimeter
Bolt Spacing Maximum	0 Inch 0Millimeter
Bore	1.969 Inch 50 Millimeter
Nominal Bolt Center to Center	6.3 Inch 160 Millimeter
Actual Bolt Center to Center	6.2 Inch 157Millimeter
Housing material	Cast iron
B4	9 mm
J max.	164 mm
J min.	151 mm
RG	1/4-28 UNF
R1	3.5 mm
Rα	45 °
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
J6	190 mm
J7	21 mm
N4	4 mm
Basic dynamic load rating C	35.1 kN
Basic static load rating C0	23.2 kN
Fatigue load limit Pu	0.98 kN
Limiting speed	4000 r/min
Mass bearing unit	2.75 kg
Thread grub screw G2	M10x1
Hexagonal key size for grub screw N	5 mm
Recommended tightening torque for grub screw	16.5 N·m
Recommended diameter for attachment bolts, mm G	16 mm

Recommended diameter for attachment bolts, inch G	0.625 in
Housing	SYJ 510
Bearing	YAR 210-2F