

# AST SA60ES plain bearings

Our TIMKEN Manufacturer Name highly-skilled and factory-trained service experts have the resources to help you with all your AST SA60ES plain bearings needs – including routine maintenance, major repairs, warranty service, and 0.0 Inventory equipment inspections.

|                           |                          |
|---------------------------|--------------------------|
| Inventory                 | 0.0                      |
| Manufacturer Name         | TIMKEN                   |
| Minimum Buy Quantity      | N/A                      |
| Weight                    | 5.897                    |
| EAN                       | 0087796305731            |
| Product Group             | M06288                   |
| Number of Mounting Holes  | 2                        |
| Mounting Method           | Tapered Adapter Sleeve   |
| Housing Style             | 2 Bolt Pillow Block      |
| Rolling Element           | Spherical Roller Bearing |
| Housing Material          | Cast Iron                |
| Expansion / Non-expansion | Non-expansion            |
| Mounting Bolts            | 1/2 Inch                 |
| Relubricatable            | Yes                      |
| Insert Part Number        | 22210K                   |
| Seals                     | Triple Ring Labyrinth    |
| Housing Configuration     | 2 Piece Split            |
| Inch – Metric             | Inch                     |
| Other Features            | Double Row               |

|                               |  |
|-------------------------------|--|
| Long Description              | 2 Bolt Pillow Block; 1-3/4" Bore; 2-1/2" Base to Center Height; Tapered Adapter Sleeve Mou |
| UNSPSC                        | 31171511   |
| Harmonized Tariff Code        | 8483.20.40.80  |
| Noun                          | Bearing  |
| Keyword String                | Pillow Block   |
| Manufacturer Item Number      | SAF 22510 X 1 3/4  |
| Weight / LBS                  | 13   |
| B                             | 2.5 Inch   63.5 Millimeter   |
| Nominal Bolt Center to Center | 6.8 Inch   171.5 Millimeter  |
| D                             | 3.625 Inch   92.075 Millimeter   |
| Bolt Spacing Minimum          | 6.5 Inch   165.1Millimeter   |
| Bolt Spacing Maximum          | 7 Inch   177.8Millimeter   |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter   |
| d                             | 1.75 Inch   44.45 Millimeter   |