

# AST SCE1112 needle roller bearings

QuestionAST SCE1112 needle roller bearings ? Find what you need faster by entering your information 0.0 Inventory .

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REGAL BELOIT   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 5.04   |
| EAN                       | 0662461030103  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Concentric Collar  |
| Housing Style             | 4 Bolt Square Flange Block   |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 21/32 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 2-22T  |
| Seals                     | Felt Labyrinth   |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | No Pilot   |
| Inch – Metric             | Inch   |
| Long Description          | 4 Bolt Square Flange Block;<br>2-1/8" Bore; 7.2" Bolt<br>Circle; 5-1/8" Bolt Spacing;<br>1 Pie |

|                                       |   |
|---------------------------------------|---|
| Other Features                        | Single Row   Standard Duty   Skwezloc   Has Flinger |
| UNSPSC                                | 31171501  |
| Harmonized Tariff Code                | 8483.20.40.40                                       |
| Noun                                  | Bearing   |
| Keyword String                        | Flanged   |
| Manufacturer Item Number              | SF-34T  |
| Manufacturer Internal Number          | 705438  |
| Weight / LBS                          | 11.1  |
| D                                     | 2.188 Inch   55.575<br>Millimeter                   |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter                               |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter                               |
| d                                     | 2.125 Inch   53.975<br>Millimeter                   |
| Bolt Spacing                          | 5.125 Inch   130.18<br>Millimeter                   |
| Nominal Bolt Circle Diameter<br>Round | 7.2 Inch   184 Millimeter                           |