

AST SMF106-TT deep groove ball bearings

Offer High Quality Brand 180 mm Da AST SMF106-TT deep groove ball bearings .Contact Us Online to 85.725 mm da Get Best Quote.

da	85.725 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	155.575 mm
S	4.763 mm
ba	44.45 mm
H	222.25 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
L	387.35 mm
N1	26.988 mm
R1	58.737 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	42.069 mm
Housing	SAFS 520
Bearing	22220 EK
Adapter sleeve assembly	SNW 20×3.3/8

Stabilizing ring	SR-20-17
Labyrinth ring	2 x LOR 101
PosiTrac Plus contact element	2 x B10724-102
End plug (suffix Y)	EPR 12
Max. speed for PosiTrac Plus seal	1650 r/min
P60°	141 kN
P90°	84.5 kN
P120°	52.5 kN
P150°	48 kN
P180°	57.4 kN
Pa	13.8 kN
Mass pillow block	40.4 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.875 in
Initial grease fill	181.44 g