

AST UCF 208-24E bearing units

AST UCF 208-24E bearing units Needs Analysis , Manufacturing Service 35 Outer Diameter (mm) . Get Your Free. 15x35x15.9 Size (mm)

Size (mm)	15x35x15.9
Bore Diameter (mm)	15
Outer Diameter (mm)	35
Width (mm)	15,9
d	15 mm
D	35 mm
B	15,9 mm
C	15,9 mm
a	16,3 mm
r min.	0,6 mm
da min.	19 mm
da max	19 mm
Da max.	31 mm
ra max.	0,6 mm
Basic dynamic load rating (C)	8,5 kN
Basic static load rating (C0)	5,3 kN
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359535761
Product Group	B00152
Enclosure	2 Metal Shields

Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Double Row
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	25 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch – Metric	Metric
Long Description	15MM Bore; 35MM Outside Diameter; 15.9MM Width; 2 Metal Shields; No Flush Ground; Ball Bearing; Doub
Other Features	Shell Alvania 2 Prelubricated
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Outside Diameter	1.378 Inch 35 Millimeter
Bore	0.591 Inch 15 Millimeter
Width	0.626 Inch 15.9 Millimeter