

# AXK1226 KOYO Oil lub. 15000 12x26x2mm Needle roller bearings

|                               |          |
|-------------------------------|----------|
| Bearing number                | AXK1226  |
| Size (mm)                     | 12x26x2  |
| Brand                         | KOYO     |
| Bore Diameter (mm)            | 12       |
| Outer Diameter (mm)           | 26       |
| Width (mm)                    | 2        |
| d                             | 12 mm    |
| D                             | 26 mm    |
| T                             | 2 mm     |
| ra max.                       | 0.3 mm   |
| Ea                            | 24.5 mm  |
| Eb                            | 13.0 mm  |
| Weight                        | 0.004 Kg |
| Basic dynamic load rating (C) | 10.8 kN  |
| Basic static load rating (C0) | 32.3 kN  |
| Bearing No.                   | AXK1226  |
| Dc1                           | 12       |
| Dc                            | 26       |
| Dw                            | 2        |
| Ca                            | 10.8     |
| C0a                           | 32.3     |
| Cu                            | 3.40     |
| Oil lub.                      | 15000    |
| ra(max)                       | 0.3      |

|                                    |        |
|------------------------------------|--------|
| (Refer.)Mass(kg)                   | 0.004  |
| D,d1                               | 26     |
| D1                                 | –      |
| h1(mm)                             | 1.00   |
| Washer designation                 | AS1226 |
| (Refer.)Mass(kg)                   | 0.003  |
| h(mm)                              | 2.75   |
| a(mm)                              | 0.50   |
| Washer designation                 | LS1226 |
| (Refer.)Mass(kg)                   | 0.009  |
| h(mm)                              | –      |
| rs(min)                            | –      |
| Washer designation Shaft piloted   | –      |
| Washer designation Housing piloted | –      |
| (Refer.)Mass(kg)                   | –      |