

Better Wear Resistant and Shock Resistant Slewing Drive Hse14 for Construction Machine Claw

Browse Better Wear Resistant and Shock Resistant Slewing Drive Hse14 for Construction Machine Claw Categories in the Manufacturers 0.0 Inventory Online Free. including . NSK
Manufacturer Name

Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight	0.455
EAN	0029176633195
Product Group	B04270
Enclosure	Open
Precision Class	ABEC 7 ISO P4
Material – Ball	Steel
Number of Bearings	2 (1 Pair)
Contact Angle	15 Degree
Preload	Medium
Raceway Style	1 Rib Outer Ring
Cage Material	Phenolic
Rolling Element	Ball Bearing
Mounting Arrangement	Duplex-Universal
Flush Ground	Yes
Inch – Metric	Metric

Other Features	Single Row Angular Contact Super Precision
Long Description	95MM Bore; 145MM Outside Diameter; 48MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Ball Angular Contact
d	3.74 Inch 95 Millimeter
B	1.89 Inch 48 Millimeter
D	5.709 Inch 145 Millimeter