

# Crossed Roller Slewing Bearings Without Gear Rks. 21411

What is Crossed Roller Slewing Bearings Without Gear Rks. 21411 in mechanical engineering? Manufacturing Service . Upload your CAD file for an 80.963 mm da instant.

|         |            |
|---------|------------|
| da      | 80.963 mm  |
| Da      | 160 mm     |
| Ca      | 49.809 mm  |
| A1      | 98.425 mm  |
| A2      | 206.375 mm |
| S       | 4.763 mm   |
| ba      | 40.481 mm  |
| H       | 196.85 mm  |
| H1      | 101.6 mm   |
| H2      | 41.275 mm  |
| J min.  | 263.525 mm |
| J max.  | 295.275 mm |
| L       | 349.25 mm  |
| N1      | 23.813 mm  |
| R1      | 60.325 mm  |
| R2      | 27.781 mm  |
| RG      | 3/8 NPT    |
| PG      | 1/8 NPT    |
| h       | 38.1 mm    |
| Housing | SAFS 518   |

|  |               |
|--|---------------|
| Bearing                                | 22218 EK      |
| Adapter sleeve assembly                | SNW 18×3.3/16 |
| Stabilizing ring                       | SR-18-15      |
| Taconite seal                          | TER 188       |
| End plug (suffix Y)                    | EPR 11        |
| Max. speed for Taconite seal           | 950 r/min     |
| P60°                                   | 141 kN        |
| P90°                                   | 84.5 kN       |
| P120°                                  | 53.4 kN       |
| P150°                                  | 48 kN         |
| P180°                                  | 58.7 kN       |
| Pa                                     | 10.9 kN       |
| Mass pillow block                      | 30.8 kg       |
| Cap bolt                               | 1/2-13 UNC    |
| Cap bolt recommended tightening torque | 149.1 N·m     |
| Cap bolt, SAE grade                    | 8             |
| Appropriate attachment bolt size G     | 0.75 in       |
| Initial grease fill                    | 141.75 g      |