

Crossed Roller Slewing Rings with External Gear Turntable Bearings

Enjoy High Margins on 340 Outer Diameter (mm) Competitive Pricing.Great Wholesale Products at Low 190x340x55 Size (mm) Costs.

| | |
|---------------------|------------|
| Size (mm) | 190x340x55 |
| Bore Diameter (mm) | 190 |
| Outer Diameter (mm) | 340 |
| Width (mm) | 55 |
| d | 190 mm |
| D | 340 mm |
| B | 55 mm |
| B1 | 13 mm |
| B2 | 21,5 mm |
| D1 | 295 mm |
| Da max | 323 mm |
| d1 | 244 mm |
| da max | 227 mm |
| da min | 207 mm |
| dc min | 247 mm |
| E | 306 mm |
| F | 230 mm |
| r1 min | 4 mm |
| ra max | 3 mm |
| rmin | 4 mm |

| | |
|--|--|
| s | 4,7 mm / Axial displacement facility from central position |
| – HJ238-E / Designation, L-section ring | HJ238E / Designation, Lsection ring |
| m | 23,2 kg / Weight |
| m1 | 2,17 kg |
| Cr | 680000 N / Dynamic load rating (radial) |
| C0r | 930000 N / Static load rating (radial) |
| nG | 3050 1/min / Limiting speed |
| nB | 1750 1/min / Reference speed |
| Cur | 111000 N / Fatigue limit load, radial |