

# CYSD NJ2207+HJ2207 cylindrical roller bearings

Find the discount CYSD NJ2207+HJ2207 cylindrical roller bearings online 15x32x9 Size (mm) you need . We offer ... If you check out our large selection of CYSD NJ2207+HJ2207 cylindrical roller bearings once .

|                               |                  |
|-------------------------------|------------------|
| Size (mm)                     | 15x32x9          |
| Bore Diameter (mm)            | 15               |
| Outer Diameter (mm)           | 32               |
| Width (mm)                    | 9                |
| d                             | 15 mm            |
| D                             | 32 mm            |
| B                             | 9 mm             |
| C                             | 9 mm             |
| Angle ( $\alpha$ )            | 30 °             |
| a                             | 2.3 mm           |
| r min.                        | 0.3 mm           |
| r1 min.                       | 0.15 mm          |
| 2B                            | 18 mm            |
| da min.                       | 17 mm            |
| Da max.                       | 31 mm            |
| ra max.                       | 0.15 mm          |
| Weight                        | 0.035 Kg         |
| Basic dynamic load rating (C) | 9,95 kN          |
| Basic static load rating (C0) | 6,85 kN          |
| (Grease) Lubrication Speed    | 15000 r/min      |
| Bore Type                     | Cylindrical Bore |

|                         |            |
|-------------------------|------------|
| Enclosure               | Open       |
| Configuration           | Duplex     |
| Bore Size               | 15 mm      |
| Outside Diameter        | 32 mm      |
| Width                   | 9 mm       |
| Fillet Radius/Chamfer   | 0.3 mm     |
| r1                      | 0.2 mm     |
| Dynamic Load Rating     | 9,950 N    |
| Static Load Rating      | 6,850 N    |
| Limiting Speed – Grease | 15,000 rpm |
| Limiting Speed – Oil    | 20,000 rpm |
| da1 (min)               | 17 mm      |
| da2 (min)               | 17 mm      |
| Da1 (max)               | 30 mm      |
| Da2 (max)               | 31 mm      |
| ra (max)                | 0.3 mm     |
| ra1 (max)               | 0.2 mm     |