

# CYSD RLS6 deep groove ball bearings

Request A Quote For Your 111.125 mm da Special CYSD RLS6 deep groove ball bearings Needs Today! Free Quotes. ISO 9001 certified.

da	111.125 mm
Da	230 mm
Ca	89.789 mm
A1	133.35 mm
A2	193.675 mm
S	4.763 mm
ba	65.881 mm
H	295.275 mm
H1	152.4 mm
H2	60.325 mm
J min.	371.475 mm
J max.	406.4 mm
J1	82.55 mm
L	466.725 mm
N1	25.4 mm
R1	79.375 mm
R2	36.513 mm
RG	1/2 NPT
PG	1/4 NPT
h	60.325 mm
Housing	SAW 526
Bearing	23226 CCK/W33

Adapter sleeve assembly	SNW 126×4.3/8
Stabilizing ring	SR-26-0
Labyrinth ring	2 x LOR 116
End plug (suffix Y)	EPR 15
Bearing limiting speed	2600 r/min
P60°	189 kN
P90°	113 kN
P120°	73.8 kN
P150°	68.1 kN
P180°	84.5 kN
Pa	31.2 kN
Mass pillow block	68 kg
Cap bolt	2 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Eye bolt	3/8-16 UNC
Appropriate attachment bolt size G	0.875 in
Initial grease fill	382.73 g