Double Roller Slewing Bearing for Construction Machine

What are the types 0.0 Inventory of Double Roller Slewing Bearing for Construction Machine? Manufacturing Service. Get Your Free, Instant price, design review.

| Inventory | 0.0 |
|---------------------------|--|
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 9.08 |
| EAN | 0883450195713 |
| Product Group | M06288 |
| Number of Mounting Holes | 2 |
| Mounting Method | Tapered Adapter Sleeve |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Spherical Roller Bearing |
| Housing Material | Cast Steel |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 5/8 Inch |
| Relubricatable | Yes |
| Insert Part Number | 22215 |
| Seals | Triple Lip Nitrile Rubber |
| Housing Configuration | 1 Piece Solid |
| Inch — Metric | Metric |
| Other Features | Double Row Heavy Duty |
| Long Description | 2 Bolt Pillow Block; 65MM Bore; 70MM Base to Center Height; Tapered Adapter Sleeve Mount; Spherical |

| UNSPSC | 31171511 |
|----------------------------------|--------------------------------|
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | DVP15K065SM |
| Weight / LBS | 25 |
| d | 2.559 Inch 65 Millimeter |
| D | 2.89 Inch 73.406 Millimeter |
| В | 2.756 Inch 70 Millimeter |
| Bolt Spacing Maximum | 8.625 Inch 219.075Millimeter |
| Actual Bolt Center to Center | 0 Inch OMillimeter |
| Nominal Bolt Center to Center | 7.8 Inch 199.2 Millimeter |
| Bolt Spacing Minimum | 6.875 Inch 174.625Millimeter |