

# Enduro GE 95 SX plain bearings

Request A Quote For Your Special Enduro GE 95 SX plain bearings Needs Today! Free 50 Bore Diameter (mm) Quotes. ISO 9001 50x90x20 Size (mm) certified.

Size (mm)	50x90x20
Bore Diameter (mm)	50
Outer Diameter (mm)	90
Width (mm)	20
d	50 mm
D	90 mm
B	20 mm
C	20 mm
rn	0,5 mm
a	3,28 mm
b	2,7 mm
f	2,46 mm
r min.	1,1 mm
r0 max.	0,6 mm
D1	86,79 mm
D2	96,5 mm
da min.	56,5 mm
da max	60 mm
Da max.	83,5 mm
ra max.	1 mm
Weight	0,459 Kg
Basic dynamic load rating (C)	35 kN

Basic static load rating (C0)	23,2 kN
(Grease) Lubrication Speed	7 100 r/min
(Oil) Lubrication Speed	8 500 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	0.465
EAN	0029176034688
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	50MM Bore; 90MM Outside Diameter; 20MM Outer Race Width; Open; Ball Bearing; ABEC 1   ISO P0; No Fil
Other Features	Deep Groove   With Snap Ring
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	1.0121
Inner Race Width	0 Inch   0 Millimeter

Outer Race Width	0.787 Inch   20 Millimeter
Outside Diameter	3.543 Inch   90 Millimeter
Bore	1.969 Inch   50 Millimeter
SRI	6.57
hidYobi	6210NR
LangID	1
ro	0.6
D_	90
SREX	0.025
B_	20
da min	56.5
hidTable	ecat_NSRDGB
Oil rpm	8500
SRE	6.57
Cy	5.4
mass	0.459
GRS rpm	7100
ra	1
SRIX	0.025
D_a	83.5
SRIN	-0.025
C0	23.2
fo	14.4
SREN	-0.025
DE_	82.7
Prod_Type3	DGBB_SR_NR_OT
DA_	12.7
bomp	0
Z_	10

yobi	6210NR
Dx	98
C_conv	35000
ALPHA_	0
SDM_	70
r	1.1
KBRG	6101
SBRG	2
DI_	57.3