

Excavator Caterpillar Cat320c Slewing Bearing, Slewing Ring, Swing Circle

Excavator Caterpillar Cat320c Slewing Bearing, Slewing Ring, Swing Circle Manufacturers , Online 35 mm d Wholesale 21 mm B Suppliers ! 80 mm D

d	35 mm
D	80 mm
B	21 mm
rs min	1.5 mm
Radial clearance class	C3
Mass	0.46 kg
Dynamic load, C	33.5 kN
Static load, C0	19.1 kN
Fatigue limit load, Cu	0.87 kN
f0	13.1
Nlim (oil)	10,000 rpm
Nlim (grease)	8,800 rpm
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.38 Hz
Characteristic rolling element frequency, BSF	4.03 Hz
Characteristic outer ring frequency, BPF0	3.06 Hz
Characteristic inner ring frequency, BRFI	4.94 Hz
da min	43 mm

Da max	72 mm
ra max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.441
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Nylon
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	35MM Bore; 80MM Outside Diameter; 21MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.98326
Outer Race Width	0.827 Inch 21 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	1.378 Inch 35 Millimeter
Outside Diameter	3.15 Inch 80 Millimeter