

# Excavator Caterpillar Cat320L Swing Circle, Slewing Bearing, Slewing Ring

We work closely with our Excavator Caterpillar Cat320L Swing Circle, Slewing Bearing, Slewing Ring manufacturing partners to 20 Bore Diameter (mm) bring 31 Width (mm) the best value to 20 mm d customers.

Bore Diameter (mm)	20
Width (mm)	31
d	20 mm
A	40 mm
B	31 mm
C	- mm
H	64 mm
H1	96 mm
H2	19 mm
L	64 mm
S	12,7 mm
Bolt (G)	PF 3/4
Weight	0,72 Kg
Basic dynamic load rating (C)	12,8 kN
Basic static load rating (C0)	6,65 kN
Inventory	0.0
Manufacturer Name	FYH BEARING UNITS
Minimum Buy Quantity	N/A
Weight / Kilogram	0.719
Product Group	M06110

Mounting Method	Set Screw
Housing Material	Cast Iron
Mounting Thread	3/4 Straight Pipe Female
Rolling Element	Ball Bearing
Insert Material	Steel
Expansion / Non-expansion	Non-expansion
Housing Style	Hanger Unit
Relubricatable	Yes
Insert Part Number	UC204
Seals	Double Lip Contact
Rating	Normal Duty
Other Features	Single Row   Spherical   Has Slinger
Long Description	20MM Bore; 64MM Base to Center Height; Set Screw; Hanger Unit; Cast Iron Housing; Ball Bearing; 64MM
Inch – Metric	Metric
UNSPSC	31171513
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Hanger
Manufacturer Item Number	UCHA204
Weight / LBS	1.587
Bore	0.787 Inch   20 Millimeter
Base to Center Height	2.52 Inch   64 Millimeter
Housing Outside Diameter	2.52 Inch   64 Millimeter
Housing Overall Length	3.78 Inch   96 Millimeter
Length Thru Bore	1.22 Inch   31 Millimeter