

Excavator John Deere870 Swing Circle, Slewing Ring, Slewing Bearing

Excavator John Deere870 Swing Circle, Slewing Ring, Slewing Bearing Product Brochures , 0.0 Inventory Manufacturing Service . Get Your N/A Minimum Buy Quantity Free.

| | |
|---------------------------|---|
| Inventory | 0.0 |
| Manufacturer Name | ABB MOTORS AND MECHANICAL INC |
| Minimum Buy Quantity | N/A |
| Weight | 70.76 |
| EAN | 0782475033874 |
| Product Group | M06288 |
| Number of Mounting Holes | 4 |
| Mounting Method | Concentric Collar |
| Housing Style | 4 Bolt Pillow Block |
| Rolling Element | Tapered Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 3/4 Inch |
| Relubricatable | Yes |
| Insert Part Number | S1U-DI-407 |
| Seals | Single Lip Contact |
| Housing Configuration | 2 Piece Split |
| Inch – Metric | Inch |
| Other Features | Double Row Heavy Duty Optional E-Tect Seal Double Collar With Set Screw |

| | |
|-------------------------------|---|
| Long Description | 4 Bolt Pillow Block; 4-7/16" Bore; 5-3/4" Base to Center Height; Concentric Collar Mount; |
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | P4B-DI-407 WD DBL INTERLOCK |
| Manufacturer Internal Number | 060792 |
| Weight / LBS | 139 |
| D | 6.75 Inch 171.45 Millimeter |
| B | 5.75 Inch 146.05 Millimeter |
| d | 4.438 Inch 112.725 Millimeter |
| Bolt Spacing Maximum | 16.25 Inch 412.75Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |
| Bolt Spacing Minimum | 14.375 Inch 365.125Millimeter |
| Nominal Bolt Center to Center | 15.3 Inch 389 Millimeter |