

Excavator Komatsu PC400LC-6/ PC450LC-6/7 Slewing Ring, Swing Circle, Slewing Bearing

Enjoy High Margins on Competitive Pricing.Great Wholesale 90
Bore Diameter (mm) Products at Low Costs. 90x135x35 Size (mm)

Size (mm)	90x135x35
Bore Diameter (mm)	90
Outer Diameter (mm)	135
Width (mm)	35
d	90 mm
D	135 mm
T	35 mm
d1	135 mm
r min.	1,1 mm
D1	93 mm
da min.	117 mm
Da max.	108 mm
ra max.	1 mm
Weight	1,69 Kg
Basic dynamic load rating (C)	114 kN
Basic static load rating (C0)	310 kN
(Grease) Lubrication Speed	1400 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	1.75

EAN	0029176029196
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	Non-Precision
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row With Flat Seat
Long Description	90MM Bore 1; 93MM Bore 2; 135MM Outside Diameter; 35MM Height; Ball Bearing; Single Direction; Not B
Inch – Metric	Metric
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	51218
Weight / LBS	3.72581
Height	1.378 Inch 35 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Outside Diameter	5.315 Inch 135 Millimeter
Bore 1	3.543 Inch 90 Millimeter
Bore 2	3.661 Inch 93 Millimeter
bore diameter:	90 mm
static load capacity:	70000 lbf
outside diameter:	135 mm

dynamic load capacity:	25600 lbf
overall width:	35 mm
operating temperature range:	Maximum of +120 °C
thrust bearing type:	Single-Direction
maximum rpm:	2200 rpm
outside diameter design:	Straight
cage material:	Steel Cage
separable or banded:	Separable
fillet radius:	1.1 mm
race type:	Flat
series:	51200
precision rating:	ABEC1, P0
SRI	8.57
hidYobi	51218
LangID	1
D_	135
SREX	0.065
C	114
B_	35
hidTable	ecat_NSSDTB
Oil rpm	2200
SRE	8.57
mass	1.69
GRS rpm	1400
ra	1
SRIX	0.065
D_a	108
SRIN	0
C0	310

SREN	0
D_1	93
Prod_Type3	TB_SD_WFS
da	117
DA_	15.875
Z_	20
yobi	51218
SDM_	112.5
r	1.1
T_	35
KBRG	5111