

Excavator Volvo Ec290 Swing Circle, Slewing Ring, Slewing Bearing

Online shopping Excavator Volvo Ec290 Swing Circle, Slewing Ring, Slewing Bearing 90x160x30 Size (mm) 160 Outer Diameter (mm) from a great selection at Store. ... Accessories.

Size (mm)	90x160x30
Bore Diameter (mm)	90
Outer Diameter (mm)	160
Width (mm)	30
d	90 mm
D	160 mm
B	30 mm
C	30 mm
r min.	2 mm
da min.	100 mm
Da max.	150 mm
ra max.	2.0 mm
Weight	2.15 Kg
Basic dynamic load rating (C)	96 kN
Basic static load rating (C0)	71,5 kN
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00308

Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	90MM Bore; 160MM Outside Diameter; 30MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 IS
Other Features	Deep Groove
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Bore	3.543 Inch 90 Millimeter
Outside Diameter	6.299 Inch 160 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	1.181 Inch 30 Millimeter
Bore Type	Cylindrical Bore
Configuration	Single Row
Bore Size	90 mm
Width	30 mm
Fillet Radius/Chamfer	2 mm
Dynamic Load Rating	96,000 N
Static Load Rating	71,500 N
Limiting Speed – Grease	4,000 rpm

Factor fo	14.5
Radial Clearance	0.012 to 0.036 mm
da (min)	100 mm
Da (max)	150 mm
ra (max)	2 mm