

EXT207+WB SNR A2 62.3 mm

Bearing units

| | |
|---|-----------|
| A1 | 12 mm |
| B | 37.6 mm |
| A5 | 18.8 mm |
| d1 | 51.1 mm |
| G | M6x1 |
| H1 | 89 mm |
| H2 | 64 mm |
| L1 | 78 mm |
| L3 | 64 mm |
| N1 | 16 mm |
| N2 | 37 mm |
| s1 | 36.3 mm |
| S | 18.8 mm |
| C | 25.7 kN |
| C0 | 15.2 kN |
| T min. | -20 °C |
| T max. | 100 °C |
| Recommended tightening torque for set screw | 11.5 Nm |
| Designation of housing | T207- |
| Designation of bearing | EX207G2 |
| Bearing number | EXT207+WB |
| Brand | SNR |
| Bore Diameter (mm) | 35 |
| d | 35 mm |
| A4 | 490 mm |

| | |
|-------------------------------|---------|
| P | 230 mm |
| e | 30 mm |
| L2 | 99 mm |
| s | 18.8 mm |
| SW | 12 mm |
| A | 50 mm |
| B1 | 51.1 mm |
| D2 | 55.6 mm |
| H | 212 mm |
| J | 166 mm |
| L | 429 mm |
| M | 173 mm |
| M1 | 19 mm |
| N | 12 mm |
| T | 6 mm |
| A2 | 62.3 mm |
| Weight | 8.5 Kg |
| Basic dynamic load rating (C) | 25.7 kN |