

EXT216 SNR L3 140 mm Bearing units

| | |
|---|---------|
| A2 | 51 mm |
| B | 74.6 mm |
| A5 | 37.3 mm |
| d1 | 110 mm |
| G | M10x1 |
| H2 | 111 mm |
| N2 | 70 mm |
| s1 | 64.3 mm |
| S | 37.3 mm |
| SW | 6 mm |
| C | 72.5 kN |
| C0 | 54.2 kN |
| T min. | -20 °C |
| T max. | 100 °C |
| Recommended tightening torque for set screw | 33 Nm |
| Designation of housing | T216- |
| Designation of bearing | EX216G2 |
| Bearing number | EXT216 |
| Brand | SNR |
| Bore Diameter (mm) | 80 |
| d | 80 mm |
| L4 | 121 mm |
| L5 | 32 mm |
| L2 | 21 mm |
| L3 | 140 mm |

| | |
|-------------------------------|---------|
| s | 37.3 mm |
| A | 70 mm |
| A1 | 51 mm |
| B1 | 95.2 mm |
| D2 | 110 mm |
| H | 184 mm |
| H1 | 111 mm |
| L | 235 mm |
| L1 | 79.5 mm |
| N | 41 mm |
| N1 | 70 mm |
| Thread (G) | M10×1 |
| J1 | 26 mm |
| J2 | 165 mm |
| Weight | 8.6 Kg |
| Basic dynamic load rating (C) | 72.5 kN |