

EXT306 SNR L 137 mm Bearing units

| | |
|---|----------|
| A2 | 28 mm |
| B | 36.5 mm |
| A5 | 19 mm |
| d1 | 50 mm |
| G | M6x1 |
| H2 | 70 mm |
| N2 | 41 mm |
| s1 | 35.75 mm |
| S | 17.5 mm |
| SW | 4 mm |
| C | 27 kN |
| C0 | 15.2 kN |
| T min. | -20 °C |
| T max. | 100 °C |
| Recommended tightening torque for set screw | 11.5 Nm |
| Designation of housing | T306- |
| Designation of bearing | EX306G2 |
| Bearing number | EXT306 |
| Brand | SNR |
| Bore Diameter (mm) | 30 |
| d | 30 mm |
| L4 | 74 mm |
| L5 | 18 mm |
| L2 | 16 mm |
| L3 | 85 mm |

| | |
|-------------------------------|---------|
| s | 17.5 mm |
| A | 41 mm |
| A1 | 28 mm |
| B1 | 50 mm |
| D2 | 50 mm |
| H | 100 mm |
| H1 | 70 mm |
| L | 137 mm |
| L1 | 48 mm |
| N | 28 mm |
| N1 | 41 mm |
| Thread (G) | M6x1 |
| J1 | 16 mm |
| J2 | 90 mm |
| Weight | 1.9 Kg |
| Basic dynamic load rating (C) | 27 kN |