

EXT311 SNR N 39 mm Bearing units

| | |
|---|---------|
| A2 | 44 mm |
| B | 55.6 mm |
| A5 | 27.8 mm |
| d1 | 83 mm |
| G | M6x1 |
| H2 | 105 mm |
| N2 | 66 mm |
| s1 | 50 mm |
| S | 27.8 mm |
| SW | 5 mm |
| C | 71.5 kN |
| C0 | 44.8 kN |
| T min. | -20 °C |
| T max. | 100 °C |
| Recommended tightening torque for set screw | 22 Nm |
| Designation of housing | T311- |
| Designation of bearing | EX311G2 |
| Bearing number | EXT311 |
| Brand | SNR |
| Bore Diameter (mm) | 55 |
| d | 55 mm |
| L4 | 115 mm |
| L5 | 29 mm |
| L2 | 23 mm |
| L3 | 127 mm |

| | |
|-------------------------------|---------|
| s | 27.8 mm |
| A | 66 mm |
| A1 | 44 mm |
| B1 | 73 mm |
| D2 | 83 mm |
| H | 163 mm |
| H1 | 105 mm |
| L | 207 mm |
| L1 | 69.5 mm |
| N | 39 mm |
| N1 | 66 mm |
| Thread (G) | M6x1 |
| J1 | 22 mm |
| J2 | 150 mm |
| Weight | 6.5 Kg |
| Basic dynamic load rating (C) | 71.5 kN |